

Amendments to the Claims

Please amend Claims 1 and 50, and add Claims 55 and 56 to read as follows.

1. (Currently Amended) A liquid transfer device ~~transferring liquid~~ for enhancing durability of an image ~~onto~~ on a printed surface of a printed product printed with ink, comprising:

a liquid transfer member having a liquid to be transferred onto the printed surface of the printed product;

a transfer surface ~~contacting~~ that is adapted to contact the printed surface of the printed product and ~~transferring transfer~~ the liquid onto the printed surface of the printed product[.];

~~said liquid transfer member including~~

a liquid accumulating portion accumulating the liquid; ~~and~~

a restricting portion, formed from a porous film formed with fine pores, supplying configured to supply the liquid in said liquid accumulating portion to said transfer surface with restriction[.]; and

a lid adapted to cover the printed product,

wherein said porous film has a thickness of 10 to 200  $\mu\text{m}$ , and diameters of the fine pores are in the range of 0.1 to 1  $\mu\text{m}$ ,

wherein the liquid in the liquid accumulating portion is supplied to the

printed product through the porous film by a depression force applied through said lid, and

wherein the liquid is at least one selected from a group consisting of fatty acid ester, silicon oil, modified silicon and fluorinated oil.

2. (Canceled).

3. (Previously Presented) The liquid transfer device as claimed in claim 1, further comprising a holding member for receiving and holding said liquid transfer member.

4. (Original) The liquid transfer device as claimed in claim 1, wherein said liquid accumulating portion is formed from a sheet form member having uniform density.

5. (Previously Presented) The liquid transfer device as claimed in claim 3, wherein said holding member includes a surface supporting frame formed with an opening portion exposing said restricting portion and a dish shaped receptacle member having a flange mating with a lower surface of said surface supporting frame, and said liquid transfer member is received within a receptacle space defined by said receptacle member and said surface supporting frame.

6. (Previously Presented) The liquid transfer device as claimed in claim 1, wherein said liquid accumulating portion is formed from a sheet form member having a different density in a thickness direction thereof.

7. (Previously Presented) The liquid transfer device as claimed in claim 6, wherein said liquid accumulating portion is formed from a sheet form member provided with treatment for continuously varying a density in the thickness direction with a predetermined gradient.

8. (Original) The liquid transfer device as claimed in claim 6, wherein said liquid accumulating portion is formed by laminating a plurality of sheet form members having different densities.

9. (Previously Presented) The liquid transfer device as claimed in claim 1, wherein capillary forces of said liquid accumulating portion, said porous film and the printed surface of said printed product are set for establishing a relationship:

liquid accumulating portion < porous film < printed surface of printed product.

10. (Previously Presented) The liquid transfer device as claimed in claim 8, wherein densities of respective sheet form members forming said liquid

accumulating portion are set for producing a greater capillary force at a closer position to said transfer surface.

11. (Previously Presented) The liquid transfer device as claimed in claim 7, wherein said liquid accumulating portion is formed with a first layer and a second layer having different densities, said first layer is located at a position more distant from said transfer surface than said second layer, and said first layer has a greater density than said second layer.

12. (Previously Presented) The liquid transfer device as claimed in claim 11, which further comprises a holding member receiving said liquid transfer member, said holding member including a surface supporting frame having an opening portion, into which said first layer covered with said restricting portion is inserted, and a dish shaped receptacle member having a flange mating with a lower surface of said surface supporting frame,

wherein said second layer is received within a receptacle space defined by said receptacle member and said surface supporting frame, said first layer covered by said restricting portion projects upwardly from a surface of said surface supporting frame, and a surface of said restricting portion forms a transfer zone.

13. (Original) The liquid transfer device as claimed in claim 11,

wherein said first layer and said second layer are formed from a fibrous body or a foamed sponge body, a density of said first layer is in a range of 0.05 to 0.5 g/cc, and a density of said second layer is in a range of 0.01 to 0.2 g/cc.

14. (Canceled).

15. (Previously Presented) The liquid transfer device as claimed in claim 1, wherein said liquid transfer member has a normally flat transfer surface, when the printed product is mounted and urged onto said transfer surface, said liquid accumulating portion is elastically deformed corresponding to a curved shape of the printed surface of the printed product so that the curved printed surface and said transfer surface are contacted over entire area.

16. (Original) The liquid transfer device as claimed in claim 15, wherein stripe form grooves are formed on a bottom surface of said liquid accumulating portion.

17.-49. (Canceled).

50. (Withdrawn-Currently Amended) A liquid transfer method for ~~transferring liquid~~ enhancing durability of an image to on a printed surface of a printed

product printed with ink, comprising the steps of:

providing a liquid accumulating portion and a restricting portion, the liquid accumulating portion accumulating the liquid and a the restricting portion being configured to restrictingly ~~supplying~~ supply the liquid in the liquid accumulating portion to a transfer surface ~~contacting~~ that is adapted to contact the printed surface of the printed product; and

transferring the liquid supplied through the restricting portion onto the printed surface of the printed product by mounting the printed surface of the printed product on the transfer surface in contact therewith and by applying a depression force through a lid that covers the printed product,

wherein the restricting portion is formed from a porous film formed with fine pores, the porous film having a thickness of 10 to 200  $\mu\text{m}$  and diameters of the fine pores being in the range of 0.1 to 1  $\mu\text{m}$ , and

wherein the liquid is at least one selected from a group consisting of fatty acid ester, silicon oil, modified silicon and fluorinated oil.

51. (Withdrawn) The liquid transfer method as claimed in claim 50, wherein the printed surface of the printed product has an area greater than the transfer surface, and the printed surface is contacted with the transfer surface dividedly for a plurality of times.

52.-54. (Canceled).

55. (New) The liquid transfer device according to claim 1, wherein the printed product has an ink receptacle layer containing silica particles or aluminum oxide particles.

56. (New) The liquid transfer method according to claim 50, wherein the printed product has an ink receptacle layer containing silica particles or aluminum oxide particles.